# NC 600mm Noodle Cookers


## LUUS

### Technical Specifications for NC-60, NC-60-A.



### 🖲 ASIAN

- Ideal for high volumes of noodles/vegetables/pasta
- Adjustable thermostat accurately controls water temp
- Includes pilot, FFD, piezo and high temp cutout
- Water purifying overflow system
- Marine grade 316 stainless steel tank
- 50 litre tank capacity
- Cabinet design with convenient front panel controls
- Supplied with 9 noodle baskets
- Modular Professional series design
- 24 month 'Platinum Warranty'
- Easy to clean and service



	<u>Model</u>	<u>Description</u>	<u>Nat Gas</u>	<u>LP Gas</u>
000	NC-60	9 basket noodle cooker	78 mj	78 mj
8	NC-60-A	6 basket & 2 soup pots	78 mj	78 mj

#### Noodle Cooker

- 78 mj jet burner with pilot, FFD and piezo ignition
- Adjustable thermostat accurately controls water temp
- Water purifying overflow system to remove excess starch
- High temperature cut-out safety mechanism
- Marine grade 1.5mm 316 stainless steel tank
- 50 litre tank capacity
- Tank filter insert 0.9mm 304 stainless steel
- Drain back basket stand 1.2mm 304 stainless steel
- Fixed position rear water spout for efficient tank filling
- Includes 9 baskets 0.7mm 304 perforated stainless steel
- Safety release tank drainage valve at bottom of unit

#### **Overall Construction**

- Heavy duty construction
- Constructed 0.9mm 304 stainless steel door
- Fiberfrax Durablanket insulation on both sides of tank
- Welded 1.2mm 304 stainless steel front hob
- Front and side panels 0.9mm 304 stainless steel
- Splashback 1.2 mm 304 stainless steel
- Includes stainless steel legs with 55mm adjustable range

#### **Dimensions**

- 600mm x 800mm x 1100mm H
- Working height 900mm
- Weight 84kg
- Packed dimensions 640mm x 860mm x 1260mm H
- Packed weight 104kg

#### **Connections**

- Gas 3/4" BSP male
- Gas 180mm from right, 70mm from rear, 150mm from floor
- Supplied with gas regulator (specify Nat or LP on order)
- Water inlet 1/2" copper tube
- Water 60mm from left, 70mm from rear, 80mm from floor
- Drain 1" BSP male
- Drain 300mm from left, 210mm from front, 220mm floor

#### Cleaning & Servicing

- Easy access to all parts & components from front
- Removable baskets and inserts

#### **Options/Accessories**

- Additional noodle baskets
- Joining caps
- RH and LH side shields
- Rear castors

