

Commercial Kitchen Equipment

TOP MOUNT S SERIES

www.cheapwok.com.au

SRT45-4

____ FEATURES / BENEFITS ____

HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure are foamed-in-place using high density, CFC free polyurethane insulation.

HOT GAS CONDENSATE SYSTEM

Through SKIPIO's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but thoroughly prevents the overflow of condensate water.

EFFICIENT REFRIGERATION SYSTEM

SKIPIO's refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

EXTERIOR & INTERIOR OF CABINET CONSTRUCTION

Stainless steel exterior (galvanized steel top, bottom, and back) and stainless steel with AL inside walls and door liners. It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury.

ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

DIGITAL TEMPERATURE CONTROL SYSTEM

It provides precise and constant temperature. This level of precision allows the displayed foods to remain fresh over an extended period of time.



Model	Swing Door	Capacity (Liters)	Shelves	Compressor (HP)	Amps (A)	Net Weight (Kg)	L X D X H (mm)
SRT45-4	4	1210	6	1/3	3.5	142	1260 x 850 x 1926

Model: SRT45-4

SPEC SHEET	SRT45-4		
Classification	Refrigerator		
Cabinet Dimension	1260x850x1926		
(WxDxH mm)			
Capacity (Liters)	1210		
Inner Temperature	1°C~8°C		
Doors	4		
Number of Shelves	6		
Refrigent	R-134a		
Compressor (Hp)	1/3		
Cooling Type	Fan cooling type		
Insulation Type	Polyurethane / Cyclopentane + CFC Free		
insulation Type			
Temperature Control Type	Digital		
Amps (A)	3.5		
Voltage (V/Hz/Ph)	240V 50Hz 1Ph		
Power (W)	366		
Weight (Kg)	142		



