

TOP MOUNT S SERIES

SRT65-3

FEATURES

HIGH-DENSITY POYLURETHANE INSULATION

The entire cabinet structure are foamed-in-place using high density, CFC free polyurethane insulation.

HOT GAS CONDENSATE SYSTEM

Through SKIPIO's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

EFFICIENT REFRIGERATION SYSTEM

SKIPIO Undercounter series refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

EXTERIOR & INTERIOR OF THE CABINET

SKIPIO Undercounter series boasts a stainless steel exterior (galvanized steel back and bottom.) Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

DIGITAL TEMPERATURE CONTROL SYSTEM

It provides precise and constant temperature. This level of precision allows the displayed food to remain fresh over an extended period of time.











TOP MOUNT S SERIES

| MODEL | SRT65-3 |
|---------------------------------|--|
| Classification | Refrigerator |
| Cabinet Dimension (WxDxH mm) | 1900 x 850 x 1937 |
| Capacity(Liters) | 1876 |
| Inner Temperature(°C) | -2°C~8°C |
| Ambient Temperature(°C) | 40 |
| Refrigent | R-134A |
| Insulation Type | Polyurethane/ Cyclopentane + CFC Free |
| Amps(A) | 6A |
| Voltage(V/Hz/Ph) | 240V / 50Hz / 1PH |
| Weight(Kg) | 167 |
| Power(W) | 732W |
| Number of Doors | 3 |
| Compressor(HP) | 3/4 |
| Number of Shelves | 9 |
| Power plug | 10A |

PLAN VIEW









