



FED-X S/S Two Door Upright Freezer - XURF650S1V

Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Ebm-papst evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 624mm W x 702mm D x 1401mm H
- 1/2 split door system can lower yearly running cost by up to 30%

Description

FED-X Stainless Steel Two Door Upright Freezer - XURF650S1V

- Net Capacity: 650L
- Cooling System: Fan forced cooling
- Temperature range: -18 ° ~-22 ° C
- Compressor: Embraco/Secop
- Controller: Dixell
- Ambient Temperature: 43 ° C
- RH: 40%
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Ebm-papst evaporator and condenser fans
- Heavy duty castors with front wheel brakes

- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 624mm W x 702mm D x 1401mm H
- 1/2 split door system can lower yearly running cost by up to 30%

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Net Weight (Kg)	126
Width (mm)	740
Depth (mm)	830
Height (mm)	2000
Packing Width (mm)	765
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V, 495W/10A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice